

Reference

Manchester Metropolitan University, Manchester



Uponor participace



TABS

Manchester Metropolitan University, Manchester

The innovative building, incorporates three individual towers and two atria and boasts not only world-class teaching and learning facilities for students, staff and businesses, but also catering and leisure areas for all students, and conference venues which will draw companies and industry associations from across Europe and beyond.

Projektová fakta:

Location	Dokončení
Manchester, United Kingdom	2012
Typ budovy	Product systems
Sportovní zařízení (venkovní/vnitřní)	Plošné vytápění a chlazení

Typ projektu

Novostavba

The solution

The innovative building, which is due to open in 2012, incorporates three individual towers and two atria and will boast, not only world-class teaching and learning facilities for students, staff and businesses, but also catering and leisure areas for all students, and conference venues which will draw companies and industry associations from across Europe and beyond.

Designed by award-winning, sustainable design firm, Feilden Clegg Bradley Studios, and built by Sir Robert McAlpine the building will top eight storeys along the Mancunian Way and slope to four at its entrance on Grosvenor Park. It will also have strong green credentials with the use of renewable energy sources, energy efficient heating

and lighting as well as a pioneering chilled concrete slab cooling system (Uponor - Thermally Active Building System TABS).

The building has been certified 'Excellent' under the BREEAM environmental assessment scheme. The total cost of the project will be £75 million and is an integral part of the University's estates investment strategy.

The Benefits

Working alongside precast manufacturer Hanson, the solution that was delivered to the scheme was a pre-cast concrete floor slab system which has a fair faced permanent formwork concrete soffit with Uponor chilled water pipework embedded beneath the soffit surface. With ground water utilised as a cooling source, a chilled water circuit in turn is passed through the concrete, creating a radiant space cooling system.

Mechanical ventilation is provided to the majority of areas using the raised access floor as a supply plenum. Return air passes into the atrium via cross talk attenuators where it rises to the air handling plant rooms at roof level for heat recovery. Cooling is provided by a combination of cooled

uponor

Kontaktujte nás

Uponor, s.r.o.
Zelený pruh 95/97
140 00 Praha 4 - Braník
Česká republika

Telefon +420 233 313 844
E-mail zakaznickyservis@uponor.com
W www.uponor.com