υροποι


QS-style copper adapters

| Job name: | Location: |
|--------------------------------|-----------------|
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |
| | |

| l echnical data | |
|-------------------------|-------------------------------------|
| Material | Brass |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Product information and application use

The Uponor QS-style Copper Adapters, combined with the appropriate QS-style Fitting Assembly, transition Wirsbo hePEXTM or Uponor AquaPEX® tubing to $1/\!\!\!2"$ and $3/\!\!4"$ copper pipe in hydronic heating applications.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | End Type 1 | End Type 2 |
|--|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|----------------------|------------------|
| QS-style Copper Adapter, R20 x 3/4" Copper | A4332075 | 0.512 | 0.275 | 0.612 | 1.224 | 1.399 | 1.063 | 0.612 | 0.531 | ISO 228-G 3/4" | Sweat 3/4" |
| QS-style Copper Adapter, R25 x 3/4" Copper (for 3/4" and 5/8" tubing only) | A4332575 | 0.599 | 0.299 | 1.038 | 1.585 | 1.375 | 1.936 | 1.309 | 1.124 | ISO 228-G 1" | Sweat 3/4" |
| QS-style Copper Adapter, R20 x 1/2" Copper | A4332050 | 0.527 | 0.26 | 0.512 | 1.224 | 1.299 | 1.063 | 0.612 | 0.531 | ISO 228-G 3/4" | Sweat 1/2" |

| Part name | Part no. | Weight per UOM [lbs/UOM] |
|--|----------|--------------------------|
| QS-style Copper Adapter, R20 x 3/4" Copper | A4332075 | 0.14 |
| QS-style Copper Adapter, R25 x 3/4" Copper (for 3/4" and 5/8" tubing only) | A4332575 | 0.3 |
| QS-style Copper Adapter, R20 x 1/2" Copper | A4332050 | 0.14 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|-------|-------------------|----------|
| QS-style copper adapters | All | - | ASTM F877 | - |
| In addition, the following parts have a | additional codes, standards, or listings: | | | |
| QS-style Copper Adapter, R20 x 3/4" Copper | A4332075 | | R20: ISO 228-G ¾" | |
| QS-style Copper Adapter, R25 x 3/4" Copper (for 3/4" and 5/8" tubing only) | A4332575 | | R25: ISO 228-G 1" | |
| QS-style Copper Adapter, R20 x 1/2" Copper | A4332050 | | R20: ISO 228-G ¾" | |
| | A4332050 | | R20: ISO 228-G ¾" | |

| Installation | Related applications |
|--|-------------------------------------|
| The corresponding compression fitting threads onto the R20 or R25 thread to adapt to copper. For additional information, refer to the Uponor Radiant Floor Heating Installation Handbook. | Radiant Heating and Cooling Systems |
| | Permafrost Protection Systems |
| | Turf Conditioning Systems |

| Footnotes | Contact i | Contact information | | | |
|-----------|------------------------|-------------------------|--|--|--|
| | Uponor Inc. | Uponor Ltd. | | | |
| | 5925 148th Street West | 6510 Kennedy Road | | | |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | | |
| | T 800.321.4739 | T 888.594.7726 | | | |
| | F 952.891.2008 | F 800.638.9517 | | | |
| | | | | | |