

# Pre-insulated Wirsbo hePEX coils

## Project Information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

## Technical data

|                       |  |
|-----------------------|--|
| Material              | PEX  |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |

## Product Information and application use

Pre-insulated Wirsbo hePEX™ complies with the most recent versions of ASHRAE 90.1 and the International Energy Conservation Code (IECC). The product is available with ½" to 1½" oxygen-barrier PEX-a service pipe covered in ½" to 1½" insulation. The insulation features manufactured-sealed seams running the entire length of the pipe for added convenience and system performance. Check with local code authorities regarding energy-code requirements for specific applications.



Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name  | Part no. | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | R value | Weight per UOM [lbs/UOM] |
|--|----------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|---------|--------------------------|
| 1/2" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil     | A6140500 | 19                         | 30                         | 8.5               | 0.475                      | 0.625                      | 3.9     | 8                        |
| 3/4" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil     | A6140750 | 19                         | 32                         | 12.5              | 0.671                      | 0.875                      | 3.6     | 12.8                     |
| 1" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil       | A6141000 | 19                         | 31                         | 12.5              | 0.862                      | 1.125                      | 3.4     | 21                       |
| 3/4" Pre-insulated Wirsbo hePEX with 1" insulation, 100-ft. coil       | A6150750 | 19                         | 39                         | 12.5              | 0.671                      | 0.875                      | 7.9     | 22                       |
| 1" Pre-insulated Wirsbo hePEX with 1" insulation, 100-ft. coil         | A6151000 | 19                         | 40                         | 14                | 0.862                      | 1.125                      | 6.4     | 30.2                     |
| 1 1/4" Pre-insulated Wirsbo hePEX with 1" insulation, 100-ft. coil     | A6151250 | 27                         | 40.5                       | 12                | 1.054                      | 1.375                      | 6.1     | 39.2                     |
| 3/4" Pre-insulated Wirsbo hePEX with 1 1/2" insulation, 100-ft. coil   | A6160750 | 27                         | 46.5                       | 12                | 0.671                      | 0.875                      | 10.3    | 29                       |
| 1" Pre-insulated Wirsbo hePEX with 1 1/2" insulation, 100-ft. coil     | A6161000 | 27                         | 49.5                       | 12                | 0.862                      | 1.125                      | 9.57    | 37.5                     |
| 1 1/4" Pre-insulated Wirsbo hePEX with 1 1/2" insulation, 100-ft. coil | A6161250 | 27                         | 52.5                       | 12                | 1.054                      | 1.375                      | 9.04    | 46.3                     |
| 1 1/2" Pre-insulated Wirsbo hePEX with 1 1/2" insulation, 75-ft. coil  | A6161500 | 27                         | 55.5                       | 12                | 1.244                      | 1.625                      | 11.2    | 49.5                     |

| Part name                        | Part no. | Codes   | Standards  | Listings  |
|----------------------------------|----------|---|--|---|
| Pre-insulated Wirsbo hePEX coils | All      | IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC | ASTM F1960 ASTM F876 ASTM F2023 ASTM E814 ULC S115 ASTM F877 CSA B137.5 CSA B214 NSF/ANSI/CAN 61 NSF/ANSI 14 | IAPMO-ES ICC-ES-PMG cNSF-us-rfh cNSF-us-pw CCMC PPI TR-4 CSA U.P.Code |

In addition, the following parts have additional codes, standards, or listings:

|  |          |          |                |
|--|----------|----------|----------------|
| 1/2" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil | A6140500 | ULC S101 | UL cQAlus P321 |
| 3/4" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil | A6140750 | ULC S101 | UL cQAlus P321 |
| 1" Pre-insulated Wirsbo hePEX with 1/2" insulation, 100-ft. coil   | A6141000 | ULC S101 | UL cQAlus P321 |
| 3/4" Pre-insulated Wirsbo hePEX with 1" insulation, 100-ft. coil   | A6150750 | ULC S101 | UL cQAlus P321 |
| 1" Pre-insulated Wirsbo hePEX with 1" insulation, 100-ft. coil     | A6151000 | ULC S101 | UL cQAlus P321 |

**Installation**

Use ProPEX® fittings to connect the piping. Refer to the ProPEX Connections Instructional Guide or the Uponor Radiant Floor Heating Installation Handbook for additional information.

**Related applications**

Pre-Insulated Pipe Systems  
Radiant Heating and Cooling Systems  
Hydronic heating and cooling systems  
Permafrost Protection Systems  
Turf Conditioning Systems

**Footnotes**

-

**Contact information**

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517