

Pre-insulated Uponor AquaPEX coils

Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|--|
| Material | PEX |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |

Product Information and application use

Pre-insulated Uponor AquaPEX® complies with the most recent versions of ASHRAE 90.1 and the International Energy Conservation Code (IECC). The product is available with ½" to 1¼" PEX-a service pipe covered in ½" or 1" insulation. The insulation features manufactured-sealed seams running the entire length of the pipe for added convenience and system performance. Check with local code authorities regarding energy-code requirements for specific applications.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | R value | Weight per UOM [lbs/UOM] |
|--|----------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|---------|--------------------------|
| 1/2" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040500 | 19 | 30 | 8.5 | 0.475 | 0.625 | 3.9 | 8 |
| 1/2" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150500 | 19 | 36 | 12.5 | 0.475 | 0.625 | 7.5 | 11 |
| 3/4" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040750 | 19 | 32 | 12.5 | 0.671 | 0.875 | 3.6 | 12.8 |
| 1" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6041000 | 19 | 31 | 12.5 | 0.862 | 1.125 | 3.4 | 21 |
| 1" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151000 | 19 | 40 | 14 | 0.862 | 1.125 | 6.4 | 30.2 |
| 1 1/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151250 | 27 | 40.5 | 12 | 1.054 | 1.375 | 6.1 | 39.2 |
| 2" Pre-insulated Uponor AquaPEX with 1 1/2" insulation, 75-ft. coil | F6162000 | 42 | 61.5 | 18 | 1.629 | 2.125 | 9.9 | 74.3 |
| 3/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150750 | 19 | 39 | 12.5 | 0.671 | 0.875 | 7.9 | 22 |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|---|--|--|
| Pre-insulated Uponor AquaPEX coils | All | IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC | ASTM F1960 ASTM F876 ASTM F2023 ASTM E814 ULC S115 ASTM F877 CSA B137.5 CSA B214 | IAPMO-ES ICC-ES-PMG CCMC PPI TR-4 CSA U.P.Code |
| In addition, the following parts have additional codes, standards, or listings: | | | | |
| 1/2" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040500 | | NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | cNSFus-pw UL cQAlus P321 |
| 1/2" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150500 | | NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | cNSFus-pw UL cQAlus P321 |
| 3/4" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040750 | | UL 1821 NSF-61 ULC S101 NSF-14 | UL cQAlus P321 cNSFus-pw-fs |
| 1" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6041000 | | UL 1821 NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | UL cQAlus P321 cNSFus-pw-fs |
| 1" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151000 | | UL 1821 NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | UL cQAlus P321 cNSFus-pw-fs |
| 1 1/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151250 | | UL 1821 NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw-fs |
| 2" Pre-insulated Uponor AquaPEX with 1 1/2" insulation, 75-ft. coil | F6162000 | | NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | cNSFus-pw UL cQAlus P321 |
| 3/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150750 | | UL 1821 NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14 | UL cQAlus P321 cNSFus-pw-fs |

| Installation | Related applications |
|---|---|
| <p>Approved fitting system is ProPEX®. Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide, PEX Piping Systems Design and Installation Manual (PDIM), Complete Design Assistance Manual (CDAM), Hydronic Piping Design Assistance Manual (HPDAM) or AquaSAFE™ Residential Fire Sprinkler Installation Guide for more information.</p> | <p>PEX-a Plumbing Systems Radiant Heating and Cooling Systems Hydronic Piping Systems</p> |

Notes

Operating condition limits (hydrostatic ratings):
 ½"-2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)

Operating condition limits (hydrostatic ratings):
 ½"-2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)

| Footnotes | Contact information | |
|-----------|---|---|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |