

ProPEX brass plugs

Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--|
| Material | Brass |
| End type 1 | ProPEX 5/8" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Product Information and application use

Uponor 5/8" ProPEX® Brass Plug is available for use in any hydronic heating and/or cooling system. The end of the plug is manufactured with the Uponor ProPEX Fitting for connections to Uponor crosslinked polyethylene (PEX) tubing.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | Weight per UOM [lbs/UOM] |
|--------------------------------|----------|----------|----------|----------|----------|--------------------------|
| ProPEX Brass Plug for 5/8" PEX | Q4536363 | 0.991 | 1.04 | 1.04 | 0.866 | 0.06 |

| Part name | Part no. | Codes | Standards | Listings |
|--------------------|----------|-------------------------------|---|--------------------------------|
| ProPEX brass plugs | Q4536363 | IMC IBC IRC NPC of Canada UMC | ASTM F1960 CSA B137.5 NSF/ANSI 14 ASTM F877 | IAPMO-ES ICC-ES-PMG cNSFus-rfh |

Installation

Use a 5/8" ProPEX Ring with Stop (Q4690625) for the tubing. For more information, refer to the Uponor ProPEX Connections Instructional Guide.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517