

Lead-free (LF) brass compression angle stop valves

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:


Technical data

Material	LF Brass
End type 1	Compression 1/2"
End type 2	UNEF 3/8"
Temp/pressure ratings	194 °F (90 °C) at 145 psi (10 bar)
Prop 65 label required?	Yes

Product information and application use

For point-of-use shutoff at the fixture, compression straight and angle stop valves are lead-free (LF) brass, chrome-plated, quarter-turn ball valves that include a stainless-steel insert for compression connection to 1/2" Uponor AquaPEX® pipe and a 3/8" male threaded connection for fixture risers.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	Weight per UOM [lbs/UOM]
LF Brass Compression Angle Stop Valve with PEX Stiffener, 1/2" Comp. x 3/8" OD Comp.	LF5415038	2.319	1.441	0.937	0.88	0.52	0.36	0.21

Part name	Part no.	Codes	Standards	Listings
Lead-free (LF) brass compression angle stop valves	LF5415038	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASME A112.18.1 ASTM F877 NSF/ANSI/CAN 372 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-pw-G U.P.Code

Installation

Install valves according to local building code. Use only the stainless steel inserts supplied by Uponor with these compression stop valves. Substitution can result in valve connection failure. Do not dismantle. Refer to the Uponor PEX Piping Systems Design and Installation Manual or Uponor PEX Piping Systems Installation Guide for additional information. For rigid fixture riser connections, use the Uponor 3/8" OD Compression Nut and Nylon Sleeve (part number F5440380), sold separately.

Related applications

PEX-a Plumbing Systems

Footnotes	Contact information		
-	<table border="0"> <tr> <td>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</td> <td>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</td> </tr> </table>	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517		