υροποι

ProPEX lead-free (LF) brass straight stop valves


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	LF Brass
End type 1	ProPEX 1/2"
End type 2	UNEF 3/8"
Temp/pressure ratings	194 °F (90 °C) at 145 psi (10 bar)
Prop 65 label required?	Yes
Product information and applicat	ion use

Product information and application use

For point-of-use shutoff at the fixture, ProPEX[®] straight and angle stop valves are lead-free (LF) brass, chrome-plated, quarter-turn ball valves that feature an ASTM F1960 connection for 1/2" Uponor AquaPEX[®] pipe and a 3/8" male threaded connection for fixture risers.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name		Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	Weight per UOM [lbs/UOM]
ProPEX LF Brass Straight St Comp.	op Valve, 1/2" PEX x 3/8" OD	LF5865038	2.067	1.388	0.7	0.709	0.433	0.433	1.417	0.15
Part name	Part no.	Codes		Standards			Listings			
ProPEX lead-free (LF) brass straight stop valves	LF5865038	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC		ASME A112.18.1 NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14			cNSFus	cNSFus-pw-G U.P.Code		

Installation	Related applications
Install valves according to local building code. Do not dismantle. Refer to the Uponor PEX Piping Systems Design and Installation Manual or Uponor PEX Piping Systems Installation Guide for additional information. For rigid fixture riser connections, use the Uponor %" OD Compression Nut and Nylon Sleeve (part number F5440380), sold separately.	PEX-a Plumbing Systems

Footnotes	Contact i	Contact information			
	Uponor Inc.	Uponor Ltd.			
	5925 148th Street West	6510 Kennedy Road			
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4			
	T 800.321.4739	T 888.594.7726			
	F 952.891.2008	F 800.638.9517			