Uponor Wipex reducer male x female G4-G3 1009052



Application information Uponor Wipex reducer male x female Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G4-G3

1009052



Technical data

Item no EAN	7331541099011
Item no GTIN	07331541099011
Item no VVS	087836193
RSK no.	2410644
Item no NRF	8360739
Item (unit of measurement)	pce
Length (I)	58 mm
Packaging Quantity 1	1
Packaging Quantity 3	6
Packaging GTIN PL1	06414905434503
Packaging GTIN PL3	06414905445066
Item Unit Length	130
Item Unit Height	60
Item Unit Weight	1,537
Item Unit Width	130

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4 00240, Helsinki Finland

T +358 (0)20 129 211

www.uponor.com