

Uponor Vario PLUS manifold kit K1

1009209

- Including brackets, flat sealing screw connection pieces with swivel nut, thermometer and end pieces with air vent, filling and draining tap and a by-pass



Application information Uponor Vario PLUS manifold kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold kit K1

1009209



Technical data

Item no EAN	4016203841100
Item no GTIN	04016203841100
Item no VVS	466247124
RSK no.	2418963
Item no NRF	8362652
Item no LVI	2026801
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 4	248
Packaging GTIN PL1	06414905256006
Packaging GTIN PL4	06414905525454
Item Unit Length	15
Item Unit Height	320
Item Unit Weight	0,73
Item Unit Width	50

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com