


## Uponor Ecoflex Aqua Twin 32x4,4-25x3,5/175

**1018140**

- Warm tap water with circulation
- Two medium pipe PE-Xa, SDR 7,4
- Max. load 10 bar / 95°C
- PEX foam, HDPE casing
- Coloured centre profil to avoid confusion of supply and circulation



### Application information Uponor Ecoflex Aqua Twin

#### Specification

- Flexible, pre-insulated, self-compensating plastic pipe system.
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 10 (SDR 7,4)
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

#### Application


- Transport of warm tap water for buried installations.
- Tap water operating temperature 70°C based on EN 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

#### Certification

- Approval should be checked by local responsible person

## Uponor Ecoflex Aqua Twin 32x4,4-25x3,5/175

1018140



### Technical data

Item no EAN	4021598111738
Item no GTIN	04021598111738
Item no VVS	087363832
Item no LVI	3010148
Item (unit of measurement)	m
Bending radius 2	0,7 m
Packaging Quantity 1	200
Packaging GTIN PL1	06414905437429
Item Unit Length	1000
Item Unit Height	175
Item Unit Weight	2,2
Item Unit Width	175

### Documents

Page with all documents

#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)