


## Uponor Ecoflex Quattro 2x32x2,9-32x4,4-25x3,5/175

1018149

- Heating and warm tap water with circulation
- Four medium pipe PE-Xa, SDR 11 and 7,4
- Max. load 6 bar heating / 10 bar tap water / 95°C
- PEX foam, HDPE casing
- Coloured centre profil to avoid confusion between the lines



### Application information Uponor Ecoflex Quattro

#### Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) and PN10 (SDR 7,4), Oxygen tightness based on EN 15632 for heating pipes
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

#### Application


- Transport of heating and warm tap water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Tap water operating temperature 70°C based on EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex Quattro 2x32x2,9-32x4,4-25x3,5/175

1018149



### Technical data

Item no EAN	4021598111790
Item no GTIN	04021598111790
Item no VVS	087817860
Item (unit of measurement)	m
Bending radius 2	0,8 m
Wall thickness s3	3,5 mm
Packaging Quantity 1	200
Packaging GTIN PL1	06414905437474
Item Unit Length	1000
Item Unit Height	175
Item Unit Weight	2,78
Item Unit Width	175

### Documents

Page with all documents

#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)