


Uponor Wipex fix point bushing G1

1018302

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex fix point bushing

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex fix point bushing G1

1018302



Technical data

Item no EAN	7331541099721
Item no GTIN	07331541099721
Item no VVS	087837025
RSK no.	2410652
Item no NRF	8360761
Item no LVI	1938025
Item (unit of measurement)	pce
Length (l)	54 mm
Packaging Quantity 1	1
Packaging Quantity 3	30
Packaging GTIN PL1	06414905437788
Packaging GTIN PL3	06414905446605
Item Unit Length	45
Item Unit Height	50
Item Unit Weight	0,22
Item Unit Width	45

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com