

Uponor Wipex fix point bushing G3

1018305

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex fix point bushing

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex fix point bushing G3

1018305



Technical data

Item no EAN	7331541099714
Item no GTIN	07331541099714
Item no VVS	087837080
RSK no.	2410655
Item no NRF	8360764
Item no LVI	1938080
Item (unit of measurement)	pce
Length (l)	135 mm
Packaging Quantity 1	1
Packaging Quantity 3	5
Packaging Quantity 4	240
Packaging GTIN PL1	06414905437818
Packaging GTIN PL3	06414905446636
Packaging GTIN PL4	06414905490639
Item Unit Length	102
Item Unit Height	140
Item Unit Weight	2,057
Item Unit Width	102

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com