


## Uponor Wipex coupling PN10 32x4,4-G1

**1018338**

- Connection of PE-Xa or PE pipe
- 10 bar, SDR 7,4
- Cylindric thread G" for O-ring sealing
- DR = dezincification resistance brass



### Application information Uponor Wipex coupling PN10

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex coupling PN10 32x4,4-G1

1018338



## Technical data

Item no EAN	7331541114103
Item no GTIN	07331541114103
Item no VVS	087883132
RSK no.	2410673
Item no NRF	5110374
Item no LVI	1932132
Item (unit of measurement)	pce
Length (l)	52 mm
Length (l1)	12 mm
Length (l2)	26 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging Quantity 4	1920
Packaging GTIN PL1	06414905259885
Packaging GTIN PL3	06414905259892
Packaging GTIN PL4	06414905259908
Item Unit Length	55
Item Unit Height	50
Item Unit Weight	0,261
Item Unit Width	50

## Documents

[Page with all documents](#) 

Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)