


Uponor Wipex coupling PN10 40x5,5-G1 1/4

1018339

- Connection of PE-Xa or PE pipe
- 10 bar, SDR 7,4
- Cylindric thread G" for O-ring sealing
- DR = dezincification resistance brass



Application information Uponor Wipex coupling PN10

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex coupling PN10 40x5,5-G1 1/4

1018339



Technical data

Item no EAN	7331541114127
Item no GTIN	07331541114127
Item no VVS	087883140
RSK no.	2410674
Item no NRF	5110375
Item no LVI	1932140
Item (unit of measurement)	pce
Length (l)	61 mm
Length (l1)	16 mm
Length (l2)	30 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging Quantity 4	960
Packaging GTIN PL1	06414905259915
Packaging GTIN PL3	06414905259922
Packaging GTIN PL4	06414905259939
Item Unit Length	60
Item Unit Height	65
Item Unit Weight	0,444
Item Unit Width	52

Documents

[Page with all documents](#)


Finland

T +358 (0)20 129 211

www.uponor.com