


Uponor Wipex elbow G1-G1

1018350

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex elbow G1-G1

1018350



Technical data

Item no EAN	7331541098861
Item no GTIN	07331541098861
Item no VVS	087832008
RSK no.	2410618
Item no NRF	8362411
Item no LVI	1935025
Item (unit of measurement)	pce
Length (l1)	35 mm
Length (l2)	35 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging Quantity 4	1920
Packaging GTIN PL1	06414905260171
Packaging GTIN PL3	06414905260188
Packaging GTIN PL4	06414905260195
Item Unit Length	54
Item Unit Height	46
Item Unit Weight	0,279
Item Unit Width	53

Documents

[Page with all documents](#)


Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com