

Uponor Wipex sleeve G2-G2

1018357

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G2-G2

1018357



Technical data

Item no EAN	7331541098793
Item no GTIN	07331541098793
Item no VVS	087830012
RSK no.	2410616
Item no NRF	8360682
Item no LVI	1936050
Item (unit of measurement)	pce
Length (l)	45 mm
Packaging Quantity 1	1
Packaging Quantity 3	15
Packaging GTIN PL1	06414905437870
Packaging GTIN PL3	06414905446698
Item Unit Length	74
Item Unit Height	45
Item Unit Weight	0,413
Item Unit Width	74

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com