

Uponor Wipex sleeve G3-G3

1018358

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G3-G3

1018358



Technical data

Item no EAN	7331541098809
Item no GTIN	07331541098809
Item no VVS	087830014
RSK no.	2410617
Item no NRF	8360683
Item no LVI	1936080
Item (unit of measurement)	pce
Length (l)	55 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging Quantity 4	480
Packaging GTIN PL1	06414905437887
Packaging GTIN PL3	06414905446704
Packaging GTIN PL4	06414905490707
Item Unit Length	65
Item Unit Height	102
Item Unit Weight	0,739
Item Unit Width	102

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com