


Uponor Wipex reducer male x female G1 1/4-G1

1018368



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G1 1/4-G1

1018368



Technical data

Item no EAN	7331541099028
Item no GTIN	07331541099028
Item no VVS	087836151
RSK no.	2410636
Item no NRF	8360731
Item no LVI	1934025
Item (unit of measurement)	pce
Length (l)	36 mm
Packaging Quantity 1	1
Packaging Quantity 3	25
Packaging Quantity 4	2400
Packaging GTIN PL1	06414905437962
Packaging GTIN PL3	06414905446780
Packaging GTIN PL4	06414905490738
Item Unit Length	50
Item Unit Height	39
Item Unit Weight	0,236
Item Unit Width	50

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com