

Uponor Wipex reducer male x female G2 1/2-G2

1018373



Application information Uponor Wipex reducer male x female

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G2 1/2-G2

1018373



Technical data

Item no EAN	7331541098977
Item no GTIN	07331541098977
Item no VVS	087836174
RSK no.	2410640
Item no NRF	8360735
Item (unit of measurement)	pce
Length (l)	48 mm
Packaging Quantity 1	1
Packaging Quantity 3	6
Packaging Quantity 4	576
Packaging GTIN PL1	06414905438006
Packaging GTIN PL3	06414905446827
Packaging GTIN PL4	06414905490752
Item Unit Length	54
Item Unit Height	85
Item Unit Weight	0,705
Item Unit Width	85

Documents

[Page with all documents](#)

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com