


Uponor RS adapter S-Press 90-RS3

1029127

- Made of tin-plated brass
- Fits to all RS2 or RS3 base parts.



Application information Uponor RS adapter S-Press

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor RS adapter S-Press 90-RS3

1029127



Technical data

Item no EAN	4021598106642
Item no GTIN	04021598106642
Item no VVS	045450090
RSK no.	1899489
Item no NRF	5071235
Item no LVI	1720824
Item (unit of measurement)	pce
Length (l)	93 mm
Length (l1)	20 mm
Length (l2)	62 mm
Packaging Quantity 1	1
Packaging Quantity 4	240
Packaging GTIN PL1	06414905439379
Packaging GTIN PL4	06414905491285
Item Unit Length	80
Item Unit Height	90
Item Unit Weight	1,337
Item Unit Width	80

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com