

Uponor Vario PLUS manifold w. valve LS 1x3/4 Euro

1042420



Application information Uponor Vario PLUS manifold w. valve

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold w. valve LS 1x3/4 Euro

1042420



Technical data

Item no EAN	4016203841216
Item no GTIN	04016203841216
Item no VVS	087605131
RSK no.	2419021
Item no NRF	8362713
Item no LVI	2025024
Item (unit of measurement)	pr
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging Quantity 4	600
Packaging GTIN PL1	06414905267781
Packaging GTIN PL3	06414905267798
Packaging GTIN PL4	06414905267804
Item Unit Length	80
Item Unit Height	120
Item Unit Weight	0,272
Item Unit Width	75

Documents

[Page with all documents](#) 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com