

## Uponor RS lock pin RS3 grey

**1042922**

- made of plastic
- to lock the RS insert to the RS base part.



### Application information Uponor RS lock pin

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor RS lock pin RS3 grey

1042922



## Technical data

Item no EAN	4021598106864
Item no GTIN	04021598106864
Item no VVS	045459122
RSK no.	1877272
Item no NRF	5079073
Item no LVI	1720627
Item (unit of measurement)	pce
Packaging Quantity 1	10
Packaging Material short PL1	LDPE
Packaging Material PL1	Low density polyethylene
Packaging GTIN PL1	06414905458851
Item Unit Length	280
Item Unit Height	8
Item Unit Weight	0,004
Item Unit Width	8

## Documents

[Page with all documents](#)

## Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)