


## Uponor S-Press adapter male thread 50-R1 1/2"MT

**1046905**

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



### Application information Uponor S-Press adapter male thread

#### Specification

- with fixed press sleeve
- stop ring
- test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
- AENOR

## Uponor S-Press adapter male thread 50-R1 1/2"MT

1046905



### Technical data

Item no EAN	4021598114029
Item no GTIN	04021598114029
Item no VVS	045481445
Item (unit of measurement)	pce
Length (l)	72 mm
Length (l1)	20 mm
Length (l2)	38 mm
Z-measurement d	50 mm
Packaging Quantity 1	3
Packaging Quantity 4	1152
Packaging GTIN PL1	06414905401499
Packaging GTIN PL4	06414905401505
Item Unit Length	72
Item Unit Height	55
Item Unit Weight	0,3475
Item Unit Width	55

### Documents

Page with all documents

#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)