



Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

1060058

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



Application information Uponor Wipex adapter S-Press PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

1060058



Technical data

Item no EAN	4021598121669
Item no GTIN	04021598121669
Item (unit of measurement)	pce
Length (l)	66 mm
Length (l1)	30 mm
Length (l2)	26 mm
Packaging Quantity 1	1
Packaging Quantity 3	25
Packaging GTIN PL1	06414905412389
Packaging GTIN PL3	06414905412396
Item Unit Length	48
Item Unit Height	45
Item Unit Weight	0,244
Item Unit Width	65

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com