



## Uponor Wipex adapter S-Press PN6 40x3,7-40x4,0

**1060059**

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



### Application information Uponor Wipex adapter S-Press PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex adapter S-Press PN6 40x3,7-40x4,0

1060059



### Technical data

Item no EAN	4021598121676
Item no GTIN	04021598121676
Item (unit of measurement)	pce
Length (l)	79 mm
Length (l1)	38 mm
Length (l2)	30 mm
Packaging Quantity 1	1
Packaging Quantity 3	15
Packaging GTIN PL1	06414905412402
Packaging GTIN PL3	06414905412419
Item Unit Length	61
Item Unit Height	82
Item Unit Weight	0,409
Item Unit Width	46

### Documents

Page with all documents



#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)