

Uponor Vario PLUS insulation kit

1063207

- Insulation thickness 19 mm, 0,038 W/mK
- Length 665 mm
- Fire classification BL-s3,do (EN 13501-1)



Application information Uponor Vario PLUS insulation kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS insulation kit

1063207



Technical data

Item no EAN	4021598124400
Item no GTIN	04021598124400
Item no VVS	087604200
RSK no.	2419859
Item (unit of measurement)	set
Packaging Quantity 3	1
Packaging GTIN PL3	06414905450404
Item Unit Length	655
Item Unit Height	55
Item Unit Weight	0,32
Item Unit Width	190

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com