


Uponor Ecoflex jointing equal PN6 125x11,4-125x11,4

1078365

- Connection of PE-Xa or PE pipe
- 6 bar, SDR 11
- DR = dezincification resistance brass



Application information Uponor Ecoflex jointing equal PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex jointing equal PN6 125x11,4-125x11,4

1078365



Technical data

Item no EAN	4021598130241
Item no GTIN	04021598130241
Item no VVS	087882325
RSK no.	2282485
Item no NRF	8361337
Item no LVI	1938510
Item (unit of measurement)	pce
Length (l)	169 mm
Length (l1)	70 mm
Length (l2)	70 mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414900328265
Item Unit Length	139
Item Unit Height	170
Item Unit Weight	7,66
Item Unit Width	158

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com