

Uponor Smatrix relay module H/C M-1XX 24V

1083576

- interface to a heating/cooling source
- switch over H/C between Uponor Smatrix and H/C source
- incl. socket for DIN rail mounting, manual, mounting material
- contact: 2 change-over (CO)
- Ucoil: 24VDC
- test voltage: 5kV
- protection class: IP40
- switching voltage: 380VAC, 125VDC
- switching current: 5A@250VAC, 5A@30VDC
- contact material: Ag+Au plated
- temperature range: -40°C...+70°C



Uponor Smatrix relay module H/C M-1XX 24V

1083576



Technical data

Item no EAN	4021598131095
Item no GTIN	04021598131095
Item no VVS	466252030
RSK no.	5398343
Item no NRF	8361243
Item no LVI	2024537
Item (unit of measurement)	pce
Length (l)	80 mm
Z-measurement h	60 mm
Z-measurement w	15 mm
Packaging Quantity 1	1
Packaging Quantity 3	84
Packaging Quantity 4	2016
Packaging GTIN PL1	06414905630066
Packaging GTIN PL3	06414905630141
Packaging GTIN PL4	06414905630387
Item Unit Length	80
Item Unit Height	60
Item Unit Weight	0,041
Item Unit Width	15

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com