

## Uponor Smatrix Base PRO gateway module R-147 KNX

### 1087164

- connects a Uponor Smatrix Base PRO controller X-147 with a BMS or third-party KNX devices
- power supply: 230VAC (+10%/-15%) / 50/60Hz
- internal fuse: T5 F3.15AL 250V, 5x20 3.15A quick acting
- operating temperature: 0°C ... +45°C
- storage temperature: -20°C ... +70°C
- max. consumption: 45W
- power connection: 1m cable with europlug
- connection terminals for system bus: 0.2mm<sup>2</sup> ... 1.5mm<sup>2</sup>
- protection class: IP20 II

#### Functions:

- room temperatur from Uponor Base or third-party KNX thermostats
- room setpoint from Uponor Base or third-party KNX thermostats
- room relative humidity from Uponor Base or third-party KNX thermostats
- room floor temperatur from Uponor Base or third-party KNX thermostats
- actuator status from Uponor Base or third-party KNX system
- forced ECO from Uponor Base PRO or third-party KNX system
- pump output from Uponor Base or third-party KNX system
- boiler output from Uponor Base or third-party KNX system
- heating/cooling curve settings/circuit from Uponor Move PRO to BMS or vice versa
- heating/cooling modes from Uponor Base PRO to BMS or vice versa

#### Consisting of:

- gateway module R-147 KNX
- power supply
- mounting material (2 screws and 2 wall plugs)
- quick guide



## Uponor Smatrix Base PRO gateway module R-147 KNX

1087164



### Technical data

Item no EAN	4021598149403
Item no GTIN	04021598149403
Item no VVS	466258030
RSK no.	2987826
Item no NRF	8361094
Item no LVI	2025241
Item (unit of measurement)	pce
Length (l)	18 mm
Z-measurement h	60 mm
Z-measurement w	90 mm
Packaging Quantity 1	1
Packaging GTIN PL1	06414905440597
Item Unit Length	18
Item Unit Height	60
Item Unit Weight	0,088
Item Unit Width	90

#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)