

Uponor S-Press valve U-shaped 20

1089027

- Made of brass
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- For cold and hot tap water application



Application information Uponor S-Press valve U-shaped

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.
- if not different mentioned:
Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

Uponor S-Press valve U-shaped 20

1089027



Technical data

Item no EAN	6414905212460
Item no GTIN	06414905212460
Item (unit of measurement)	pce
Length (l)	76 mm
Length (l1)	21 mm
Length (l2)	40 mm
Length (l3)	27 mm
Z-measurement h	86 mm
Z-measurement w	63 mm
Z-measurement z2	18 mm
Packaging Quantity 1	1
Packaging Quantity 4	10
Packaging Quantity 3	60
Packaging Quantity 4	1440
Packaging GTIN PL1	06414905235131
Packaging GTIN PL2	06414905270668
Packaging GTIN PL3	06414905271740
Packaging GTIN PL4	06414905276066
Item Unit Length	58
Item Unit Height	86
Item Unit Weight	0,286
Item Unit Width	74

Documents

Page with all documents

www.uponor.com