


Uponor S-Press valve straight 25

1089029

- Made of brass
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- For cold and hot tap water application



Application information Uponor S-Press valve straight

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.
- if not different mentioned:
Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
 - DVGW
 - AENOR

Uponor S-Press valve straight 25

1089029



Technical data

Item no EAN	6414905212491
Item no GTIN	06414905212491
Item (unit of measurement)	pce
Length (l1)	48 mm
Length (l2)	54 mm
Z-measurement h	73 mm
Z-measurement z2	24 mm
Packaging Quantity 1	1
Packaging Quantity 4	10
Packaging Quantity 3	90
Packaging Quantity 4	2340
Packaging Material short PL1	LDPE
Packaging Material short PL2	PAP
Packaging Material short PL3	PAP
Packaging Material PL1	Low density polyethylene
Packaging Material PL2	Corrugated fibreboard
Packaging Material PL3	Corrugated fibreboard
Packaging GTIN PL1	06414905235155
Packaging GTIN PL2	06414905270682
Packaging GTIN PL3	06414905271764
Packaging GTIN PL4	06414905276080
Item Unit Length	102
Item Unit Height	89
Item Unit Weight	0,303
Item Unit Width	35

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com