

Uponor S-Press valve straight 20

1089030

- Made of brass
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- For cold and hot tap water application



Application information Uponor S-Press valve straight

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.
- if not different mentioned:
Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

Uponor S-Press valve straight 20

1089030



Technical data

Item no EAN	6414905212507
Item no GTIN	06414905212507
Item (unit of measurement)	pce
Length (l1)	38 mm
Length (l2)	45 mm
Z-measurement h	71 mm
Z-measurement z2	23 mm
Packaging Quantity 1	1
Packaging Quantity 4	10
Packaging Quantity 3	90
Packaging Quantity 4	2970
Packaging Material short PL1	LDPE
Packaging Material short PL2	PAP
Packaging Material short PL3	PAP
Packaging Material PL1	Low density polyethylene
Packaging Material PL2	Corrugated fibreboard
Packaging Material PL3	Corrugated fibreboard
Packaging GTIN PL1	06414905235162
Packaging GTIN PL2	06414905270699
Packaging GTIN PL3	06414905271771
Packaging GTIN PL4	06414905276097
Item Unit Length	83
Item Unit Height	84
Item Unit Weight	0,213
Item Unit Width	28

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com