


## Uponor RS adapter S-Press PLUS 32-RS2

**1095820**

- tin plated
- made of DR material
- press without bevel



### Application information Uponor RS adapter S-Press PLUS

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.
- E.g.
- DVGW
  - AENOR

## Uponor RS adapter S-Press PLUS 32-RS2

1095820



### Technical data

Item no EAN	6414905480135
Item no GTIN	06414905480135
Item no VVS	045450332
RSK no.	1899576
Item no NRF	5071229
Item no LVI	1720819
Item (unit of measurement)	pce
Length (l)	75 mm
Length (l1)	20 mm
Length (l2)	28 mm
Packaging Quantity 1	1
Packaging Quantity 4	378
Packaging GTIN PL1	06414905481620
Packaging GTIN PL4	06414905555598
Item Unit Length	75
Item Unit Height	70
Item Unit Weight	0,3844
Item Unit Width	70

### Documents

Page with all documents

Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)