


Uponor Ecoflex VIP Thermo Twin 2x40x3,7 /175

1118582

- Heating and Cooling
- Two medium pipes PE-Xa with oxygen barrier, SDR11
- Max. Load 6 bar / 95°C
- Coloured centre profil to avoid confusion of flow and return line
- VIP+PEX foam, HDPE casing



Application information Uponor Ecoflex VIP Thermo Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural colored, PN 6 (SDR 11), Oxygen tightness based on EN 15632
- Insulating material: Revolutionary insulation material with extremely low lambda value in combination with permanently elastic closed-cell PE-X foam
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex VIP Thermo Twin 2x40x3,7 /175

1118582



Technical data

Item no EAN	6414905519125
Item no GTIN	06414905519125
Item no VVS	087808440
RSK no.	2266369
Item no NRF	8360959
Item no LVI	3010244
Item (unit of measurement)	m
Bending radius 2	0,8 m
Packaging Quantity 1	200
Packaging GTIN PL1	06414905542536
Item Unit Length	1000
Item Unit Height	175
Item Unit Weight	2,9
Item Unit Width	175

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com