

Uponor Minitec connection box 1x

1005270

- For single room temperature control
- Primary circuit connection 3/4" eurocone
- Max. pressure: 10 bar at 60°C



About Uponor Minitec connection box

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- for use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- EN 13501-1 fire classification: class E.
- standard flammability, building-material class B2, conforming to DIN 4102.
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application

- radiant underfloor heating and cooling
- very low construction height
- for use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Uponor Minitec connection box 1x

1005270



Technical data

Item no EAN	4021598026735
Item no GTIN	04021598026735
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 4	30
Packaging GTIN PL1	06414905432400
Packaging GTIN PL4	06414905456055
Item Unit Length	300
Item Unit Height	80
Item Unit Weight	0,2
Item Unit Width	220

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb