

## Uponor Minitec connection box 2x

**1005271**

- For single room temperature control
- Primary circuit connection 3/4" eurocone
- Max. pressure: 10 bar at 60°C



### About Uponor Minitec connection box

#### Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- for use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- EN 13501-1 fire classification: class E.
- standard flammability, building-material class B2, conforming to DIN 4102.
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m<sup>2</sup>

#### Application

- radiant underfloor heating and cooling
- very low construction height
- for use with qualified filler materials

#### Certification

- DIN CERTCO: 7F170-F

## Uponor Minitec connection box 2x

1005271



### Technical data

Item no EAN	4021598026742
Item no GTIN	04021598026742
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging GTIN PL1	06414905252008
Item Unit Length	300
Item Unit Height	80
Item Unit Weight	2
Item Unit Width	220

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)