

## Uponor Vario PLUS actuator PRO DDC 100kOhm 24V NC MT30x1,5 0-10V DC

**1005544**

- DDC for proportional control for Uponor Vario Plus manifold and valve 1005100
- first open function
- protection class: IP54
- color: white RAL9010



### About Uponor Vario PLUS actuator PRO DDC 100kOhm

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS actuator PRO DDC 100kOhm 24V NC MT30x1,5 0-10V DC

1005544



### Technical data

Item no EAN	4021598023246
Item no GTIN	04021598023246
Item no VVS	466223330
RSK no.	2987801
Item no LVI	2024320
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 3	100
Packaging Quantity 4	2000
Packaging GTIN PL1	06414905432806
Packaging GTIN PL3	06414905444434
Packaging GTIN PL4	0641490555192
Item Unit Length	55
Item Unit Height	60
Item Unit Weight	0,11
Item Unit Width	44

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)