

## Uponor Vario B by-pass WGF XL900 G1/2

1009120

- Made of brass and plastic



### About Uponor Vario B by-pass WGF

#### Specification

- Made of brass
- With integrated valves
- Connection right or left with flat sealing supply
- With lockshield valve or flowmeter for balancing and shutoff
- no primary connection to combine it with the correct accessories
- Loop connection G3/4" eurocone
- Loop distance 50 mm
- Bracket distance 210 mm

#### Application

- For underfloor heating and cooling
- Combineable with actuators FT 30x1,5
- Max. pressure: 6 bar at 60°C

## Uponor Vario B by-pass WGF XL900 G1/2

1009120



### Technical data

Item no EAN	7318793556905
Item no GTIN	07318793556905
Item no VVS	046259034
RSK no.	2418549
Item no NRF	8362456
Item no LVI	2025082
Item (unit of measurement)	pce
Packaging Quantity 1	1
Packaging Quantity 3	5
Packaging GTIN PL1	06414905434534
Packaging GTIN PL3	06414905445080
Item Unit Length	200
Item Unit Height	50
Item Unit Weight	0,496
Item Unit Width	110

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)