


Uponor Vario PLUS hose connection G3/4 x 1/2

1009214



About Uponor Vario PLUS hose connection

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application


- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS hose connection G3/4 x 1/2

1009214



Technical data

Item no EAN	4016203841827
Item no GTIN	04016203841827
Item no VVS	087602176
RSK no.	2418976
Item no NRF	8362666
Item no LVI	2026815
Item (unit of measurement)	pce
Length (l)	35 mm
Length (l1)	9 mm
Length (l2)	23 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging Quantity 4	640
Packaging GTIN PL1	06414905434701
Packaging GTIN PL3	06414905445158
Packaging GTIN PL4	06414905655939
Item Unit Length	20
Item Unit Height	30
Item Unit Weight	0,01
Item Unit Width	20

Technical documents

Download documents here

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb