


Uponor Minitec Y compression adapter 2x9,9-3/4"Euro

1016692

- Made of brass
- 3/4 Euro
- For 2 loops



About Uponor Minitec Y compression adapter

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- for use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- EN 13501-1 fire classification: class E.
- standard flammability, building-material class B2, conforming to DIN 4102.
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application


- radiant underfloor heating and cooling
- very low construction height
- for use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Uponor Minitec Y compression adapter 2x9,9-3/4"Euro

1016692



Technical data

Item no EAN	6414905515851
Item no GTIN	06414905515851
Item no VVS	381119039
RSK no.	2434387
Item no NRF	8361061
Item no LVI	2022147
Item (unit of measurement)	pce
Length (l)	64 mm
Length (l1)	13 mm
Z-measurement b	30 mm
Packaging Quantity 3	50
Packaging Material short PL3	PAP
Packaging Material PL3	Corrugated fibreboard
Packaging GTIN PL3	06414905446575
Item Unit Length	68
Item Unit Height	30
Item Unit Weight	0,2
Item Unit Width	48

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb