


Uponor Ecoflex Thermo Twin 2x32x2,9/175

1018135

- Heating and Cooling
- Two medium pipes PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 95°C
- Coloured centre profil to avoid confusion of flow and return line
- PEX foam, HDPE casing



About Uponor Ecoflex Thermo Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) or PN 10 (SDR 7,4), Oxygen tightness based on EN 15632
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo Twin 2x32x2,9/175

1018135



Technical data

Item no EAN	6414905210350
Item no GTIN	06414905210350
Item no VVS	087809032
RSK no.	2190562
Item no NRF	8360503
Item no LVI	3010233
Item (unit of measurement)	m
Bending radius 2	0,6 m
Packaging Quantity 1	200
Packaging GTIN PL1	06414905437375
Item Unit Length	1000
Item Unit Height	175
Item Unit Weight	1,99
Item Unit Width	175

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb