


Uponor Wipex coupling PN6 32x2,9-G1

1018329

- Connection of PE-Xa or PE pipe
- 6 bar, SDR 11
- Cylindric thread G" for O-ring sealing
- DR = dezincification resistance brass



About Uponor Wipex coupling PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex coupling PN6 32x2,9-G1

1018329



Technical data

Item no EAN	7331541100007
Item no GTIN	07331541100007
Item no VVS	087883032
RSK no.	2410665
Item no NRF	8362406
Item no LVI	1932032
Item (unit of measurement)	pce
Length (l)	52 mm
Length (l1)	12 mm
Length (l2)	26 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging Quantity 4	1920
Packaging GTIN PL1	06414905259625
Packaging GTIN PL3	06414905259649
Packaging GTIN PL4	06414905259656
Item Unit Length	48
Item Unit Height	55
Item Unit Weight	0,279
Item Unit Width	37

Technical documents

Download documents here

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb