

Uponor Wipex coupling PN10 50x6,9-G1 1/4

1018340

- Connection of PE-Xa or PE pipe
- 10 bar, SDR 7,4
- Cylindric thread G" for O-ring sealing
- DR = dezincification resistance brass



About Uponor Wipex coupling PN10

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex coupling PN10 50x6,9-G1 1/4

1018340



Technical data

Item no EAN	7331541114141
Item no GTIN	07331541114141
Item no VVS	087883150
RSK no.	2410675
Item no NRF	5110376
Item no LVI	1932150
Item (unit of measurement)	pce
Length (l)	68 mm
Length (l1)	16 mm
Length (l2)	37 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging Quantity 4	960
Packaging GTIN PL1	06414905259946
Packaging GTIN PL3	06414905259953
Packaging GTIN PL4	06414905259960
Item Unit Length	70
Item Unit Height	53
Item Unit Weight	0,667
Item Unit Width	75

Technical documents

Download documents here

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb