


Uponor Wipex tee G1-G1-G1

1018345

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex tee

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex tee G1-G1-G1

1018345



Technical data

Item no EAN	7331541098915
Item no GTIN	07331541098915
Item no VVS	087842008
RSK no.	2410622
Item no NRF	8362413
Item no LVI	1933025
Item (unit of measurement)	pce
Length (l1)	35 mm
Length (l2)	35 mm
Length (l3)	35 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging Quantity 4	1920
Packaging GTIN PL1	06414905260065
Packaging GTIN PL3	06414905260072
Packaging GTIN PL4	06414905260089
Item Unit Length	70
Item Unit Height	45
Item Unit Weight	0,333
Item Unit Width	60

Technical documents

Download documents here

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb