

Uponor Wipex tee G2-G2-G2

1018347

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex tee

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex tee G2-G2-G2

1018347



Technical data

Item no EAN	7331541098892
Item no GTIN	07331541098892
Item no VVS	087842012
RSK no.	2410624
Item no NRF	8360702
Item no LVI	1933050
Item (unit of measurement)	pce
Length (l1)	55 mm
Length (l2)	55 mm
Length (l3)	55 mm
Packaging Quantity 1	1
Packaging Quantity 3	4
Packaging Quantity 4	384
Packaging GTIN PL1	06414905260126
Packaging GTIN PL3	06414905260133
Packaging GTIN PL4	06414905260140
Item Unit Length	88
Item Unit Height	115
Item Unit Weight	1,025
Item Unit Width	73

Technical documents

[Download documents here](#) 

UK

T +44 (0)1923 927000
E enquiries.uk@uponor.comwww.uponor.com/en-gb