

Uponor Wipex elbow G2-G2

1018352

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex elbow G2-G2

1018352



Technical data

Item no EAN	7331541098847
Item no GTIN	07331541098847
Item no VVS	087832012
RSK no.	2410620
Item no NRF	8360692
Item no LVI	1935050
Item (unit of measurement)	pce
Length (l1)	55 mm
Length (l2)	55 mm
Packaging Quantity 1	1
Packaging Quantity 3	5
Packaging Quantity 4	480
Packaging GTIN PL1	06414905260232
Packaging GTIN PL3	06414905260249
Packaging GTIN PL4	06414905260256
Item Unit Length	98
Item Unit Height	71
Item Unit Weight	0,854
Item Unit Width	98

Technical documents

[Download documents here](#) 

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb