

Uponor Wipex elbow G3-G3

1018353

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex elbow G3-G3

1018353



Technical data

Item no EAN	7331541098854
Item no GTIN	07331541098854
Item no VVS	087832014
RSK no.	2410621
Item no NRF	8360693
Item no LVI	1935080
Item (unit of measurement)	pce
Length (l1)	75 mm
Length (l2)	75 mm
Packaging Quantity 1	1
Packaging Quantity 3	2
Packaging GTIN PL1	06414905260263
Packaging GTIN PL3	06414905260270
Item Unit Length	120
Item Unit Height	102
Item Unit Weight	2,184
Item Unit Width	120

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb