


Uponor Wipex flange F25/4-85/G1

1018359

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F25/4-85/G1

1018359



Technical data

Item no EAN	7331541099295
Item no GTIN	07331541099295
Item no VVS	087844025
RSK no.	2410645
Item no NRF	8360751
Item no LVI	1938125
Item (unit of measurement)	pce
Z-measurement k	85 mm
Packaging Quantity 1	1
Packaging Quantity 3	10
Packaging GTIN PL1	06414905437894
Packaging GTIN PL3	06414905446711
Item Unit Length	111
Item Unit Height	25
Item Unit Weight	1,245
Item Unit Width	111

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb