


Uponor Wipex reducer male x female G1 1/2-G1 1/4

1018369

**About Uponor Wipex reducer male x female****Specification**

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex reducer male x female G1 1/2-G1 1/4

1018369



Technical data

Item no EAN	7331541098946
Item no GTIN	07331541098946
Item no VVS	089770603
RSK no.	2410637
Item no NRF	8360732
Item (unit of measurement)	pce
Length (l)	39 mm
Packaging Quantity 1	1
Packaging Quantity 3	25
Packaging Quantity 4	2400
Packaging GTIN PL1	06414905437979
Packaging GTIN PL3	06414905446797
Packaging GTIN PL4	06414905490745
Item Unit Length	60
Item Unit Height	39
Item Unit Weight	0,246
Item Unit Width	60

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb